



304 Stainless Steel Fittings

Construction

- Stainless Steel Type 304 fitting, has a four piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule and body.
- Designed with an insulated throat to prevent wire damage during installation.
- Included sealing washer and stainless steel lock nut provides a means for connecting the fitting to boxes.
- Excellent corrosion resistance, strength and durability.

Installation

- Fitting is ideal for use with standard liquid-tight conduit to allow easy installation. IP 66/67 Rated when installed with approved conduit.
- Approved for both exposed and concealed locations. Rated for temperature ranges -49°F to + 221°F (-45°C to +105°C).
- Suitable for harsh industrial, food and beverage, petrochemical, waste water, salt water and other corrosive applications.
- Suitable for use in hazardous locations per NEC Articles 501 Class I Div. 2, Article 502 Class II Div. 1 & 2, Article 503 Class III Div. 1 & 2.
- Manufactured in a range of trade sizes from 3/8" through 1".
- Complies with UL Standard 514B File No. E234207.



Straight - NPT Thread 3/8" through 1"



90° - NPT Thread 3/8" through 1"



NEC Articles

- Article 501.10 (B) (2) Class I Div. 2
- Article 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
- Article 503.10 (A) (3) and (B) Class III Div. 1 & 2

www.ul.com

www.nfpa.org

www.nema.org

www.csa-international.org

www.naed.org

www.anametelectrical.com

U.L. LISTED  • CSA CERTIFIED • RoHS WEEE COMPLIANT

Stainless Steel Fittings


Type 304

Product Specifications

Ordering Information

Electrical Trade Size	K.O. Size	Dimensions					Approx Weight (lbs.)	Straight Fittings	
		Inches	mm	Inches	Inches			Standard Package	AEI PIN
3/8	12	1/2	1.457	0.512	1.024	-	3.5	25	81401292
1/2	16	1/2	1.457	0.512	1.142	-	4.4	25	81401692
3/4	21	3/4	1.575	0.591	1.379	-	2.4	10	81402092
1	27	1	1.811	0.591	1.772	-	1.5	5	81402692

Note: 1. Other sizes available on special order



Product Specifications

Ordering Information

Electrical Trade Size	K.O. Size	Dimensions						Approx Weight (lbs.)	90° Fittings	
		Inches	mm	Inches	Inches				Standard Package	AEI PIN
3/8	12	1/2	1.457	0.512	1.024	1.693	2.2	10	81491292	
1/2	16	1/2	1.457	0.512	1.142	1.693	2.8	10	81491692	
3/4	21	3/4	1.693	0.591	1.379	1.890	3.5	10	81492092	
1	27	1	1.890	0.591	1.772	2.323	2.6	5	81492692	

Note: 1. Other sizes available on special order

