

# Type UI

Capillary Armor  
Stainless Steel Stripwound Hose



### Construction

- Constructed of continuously interlocked Type 302 stainless steel core for exceptional crush and corrosion resistance.
- Product will not spring open or unwind.
- Extruded PVC, Silicone, Teflon, and Thermoplastic Rubber jackets available upon request.
- Available in brass, galvanized steel and aluminum.



Interlocked Construction

### Applications

- For applications with a max temperature of 1800°F
- Casings
- Armor
- Protection for wiring and capillary tubing
- Control cables
- Bar Dispenser casing



[www.naed.org](http://www.naed.org)

[www.nema.org](http://www.nema.org)

[www.anametelectrical.com](http://www.anametelectrical.com)



• RoHS WEEE COMPLIANT

## Type UI

Stainless Steel Stripwound Hose



### Product Specifications

### Ordering Information

Nominal Size		Inside Diameter		Outside Diameter		Approx Inside Bend Radius	Approx Weight lbs.	Standard Reel	
Inches	mm	Inches		Inches				PER	Length
		MIN.	MAX.	MIN.	MAX.	Inches	100 FT.	Feet	PIN
5/32	4	.160	.175	.255	.270	1-1/2	4.2	1000	451550-0070
3/16	5	.180	.195	.275	.290	1-1/2	4.9	1000	451554-0070
7/32	5.5	.215	.230	.310	.325	1-1/2	6.6	1500	451560-0070
1/4	6	.245	.260	.340	.355	1-1/2	7.3	800	451564-0070
5/16	8	.310	.325	.405	.420	1-1/2	8.9	500	451568-0070
3/8	9.5	.370	.390	.485	.505	2	12	500	451572-0070
7/16	11	.432	.452	.547	.567	2-1/2	14.7	500	451574-0070
1/2	12.7	.495	.515	.610	.630	2-1/2	16.5	500	451576-0070

NOTE: 1. Other sizes available on special order.  
2. Available in brass, galvanized steel and aluminum.