

CORD GRIPS, STAINLESS STEEL AND NICKEL-PLATED BRASS

SEALTITE® DOUBLE SEAL CORD GRIPS UL/CSA



DESCRIPTION

- Two clamping seals are included with each fitting, with the smaller diameter inner seal fitting inside the outer seal
- Seals are made of V0 rated EPDM rubber, tested and certified in compliance with EN45545-2, Hazard Level (HL1 / HL2 / HL3) for rail applications
- The large diameter outer seal can be used alone on large cable but smaller diameter cable requires use of both clamping seals
- Seals can also be used with braided cables for EMC applications. Before mounting, fold the braid end over the clamping seal(s)
- The extra-robust counter nut provides increased clamping strength
- Each fitting has a sealing ring and lock nut.

SPECIFICATIONS

- Stainless steel gland, male, consisting of four parts (body, counter nut and inner and outer (two-part) clamping seals)
- Body and counter nut are stainless steel AISI-316, inner and outer clamping seals are EPDM rubber
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to +105° C)
- Protection class: IP 68, NEMA 4x rated
- cULus 514B Approved QCRV.E500099

APPLICATIONS


- Suitable for rail applications HL 1, HL 2 and HL 3 according to EN 45545-2, R22 and R23, E15 and E30 according to EN 45545-3 for wall and ceiling
- Suitable for hazardous locations per NEC Articles
 - 501.10 (B) (2) Class I Div. 2
 - 502.10 (1) (2) Class II Div. 1 & 2
 - 503.10 (A) (3) and (B) Class III Div. 1 & 2

See: www.ul.com www.nfpa.org www.naed.org
www.nema.org www.anacondasealtite.com



STAINLESS STEEL AISI-316

Thread NPT	Item ID	UL/CSA* Both Seals Min. Diameter	Clamping Range Diameter (inches)		Dimensions (inches)				Weight (lbs/100)	Std. Pkg.
			Both Seals	Outer Seal	A	B	C	E		
1/2"	73871292	0.216	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2"	73871692	0.295	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4"	73871892	0.295	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4"	73872092	0.472	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1"	73872392	0.472	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1"	73872692	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4"	73873092	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4"	73873592	0.925	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2"	73873892	0.925	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2"	73874092	1.20	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2



NICKEL-PLATED BRASS

Thread NPT	Item ID	UL/CSA* Both Seals Min. Diameter	Clamping Range Diameter (inches)		Dimensions (inches)				Weight (lbs/100)	Std. Pkg.
			Both Seals	Outer Seal	A	B	C	E		
1/2"	7387122	0.216	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2"	7387162	0.295	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4"	7387182	0.295	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4"	7387202	0.472	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1"	7387232	0.472	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1"	7387262	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4"	7387302	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4"	7387352	0.925	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2"	7387382	0.925	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2"	7387402	1.20	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2

*For UL/CSA pull out strength of 36 lbs., the minimum diameter has been calculated for both seals by adding .059 inch to the normal minimum clamping diameter.

IP 68 with approved cable